


卸克

Forged Chain Shackles

SCREW PIN

G-210 S-210



BOLT TYPE

G-2150 S-2150



Size		Dimensions (mm+/-10%)										S.W.L	Weight
mm	inch	A	B	C	D	E	F	G	K	L	M	Ton	Kg
6.5	1/4	11.9	7.9	6.4	6.4	24.6	15.5	22.4	40.4	4.8	35.1	1/2	0.11
8	5/16	13.5	9.7	7.9	7.9	29.5	19.1	26.2	48.5	5.6	42.2	3/4	0.17
9.5	3/8	16.8	11.2	9.7	9.7	35.8	23.1	31.8	58.4	6.4	51.6	1	0.24
11	7/16	19.1	12.7	11.2	11.2	41.4	26.9	36.6	67.6	7.9	60.5	1 1/2	0.40
13	1/2	20.6	16.0	12.7	12.7	46.0	30.2	41.4	77.0	9.7	68.3	2	0.59
16	5/8	26.9	19.1	15.7	16.0	58.7	38.1	50.8	95.3	11.2	84.8	3 1/4	1.21
19	3/4	31.8	22.4	20.6	19.1	69.9	46.0	60.5	115.1	12.7	100.8	4 3/4	2.25
22	7/8	36.6	25.4	25.4	22.4	81.0	53.1	71.4	135.4	12.7	114.3	6 1/2	3.16
25	1	42.9	28.7	28.7	25.4	93.7	60.5	81.0	150.9	14.2	128.8	8 1/2	4.75
28	1 1/8	46.0	31.8	31.8	28.7	103.1	68.3	90.9	172.2	16.0	142.0	9 1/2	6.75
32	1 1/4	51.6	35.1	35.1	31.8	115.1	76.2	100.1	190.5	17.5	156.5	12	9.06
34	1 3/8	57.2	38.1	38.1	35.1	127.0	84.1	111.3	210.3	19.1	173.7	13 1/2	11.63
38	1 1/2	60.5	41.1	41.1	40.4	136.7	91.9	122.2	230.1	20.6	186.7	17	15.95
44	1 3/4	73.2	53.8	53.8	44.5	162.1	106.4	146.1	278.6	25.4	230.6	25	26.75
50	2	82.6	50.8	50.8	50.8	184.2	122.2	171.5	311.9	31.0	262.6	35	42.31
62	2 1/2	104.9	66.5	66.5	66.5	238.3	144.5	203.2	376.9	35.1	330.2	55	71.75